
## **EnPro**

# PPAI – PRESSURE ASSISTED INSERTION PROBE

EnPro PPAI Pipeline Insertion Probes have been designed to be fully inserted and retracted from the pipeline using pressure assistance. This enables easy and safe operation and can be carried out by one person without the need for special tools.

The PPAI is fully adjustable over its entire insertion length. If pipeline pressure source is not available or suitable for insertion assistance, a supplementary gas supply can be used.



#### Zealand.

**ENPRO** 

**ABOUT US** 

Since 1990, Haldatec has

Gas and related industries

been providing products

and services to the Oil,

in Australia, Pakistan,

Singapore, Papua New Guinea, India and New

Our house product label, EnPro, has been developed to complement our core business and has been driven by customer needs. Our comprehensive range includes innovative designs, adaptations and applications introduced to solve problems for our customers.

### **STANDARDS**

To ensure we provide the best possible support for our customers and suppliers, we have certification to ISO9001:2015.



PPAI with dispersion nozzle

The PPAI has many and varied applications including:

- Pitot probe with 'Hot Loop' return
- Corrosion Coupon
- Dispersion Nozzle
- Sample collection
- Temperature Probe
- Liquid Siphon
- Injection Probe

#### SPECIFICATIONS

temperature rating  Connections  Pipeline: 1" MNPT connection standard. Flanged connection available up to 1500 ANSI in RF, RTJ, etc. Process connection: ½" FNPT - standard  Insertion length  Construction & materials  Options  Silconert treatment (inhibits sulphur and mercury ingression) ICEx Heated version available  Weight  Up to 1500 ANSI  Pipeline: 1" MNPT connection \$1500 ANSI in RF, RTJ, etc. Process connection: ½" FNPT - standard Silconection increments of 250 mm to 2000 mm Silconert treatment (inhibits sulphur and mercury ingression) ICEx Heated version available  Weight  (Standard 1" NPT, 500 mm insertion) 7.2 kg.	SPECIFICATION	ONG
connection standard. Flanged connection available up to 1500 ANSI in RF, RTJ, etc. Process connection: ¼" FNPT - standard  Insertion length  Construction & materials  Options  Silconert treatment (inhibits sulphur and mercury ingression) ICEx Heated version available  Weight  Connection available connection available  Viton elastomer (std.)	temperature	Up to 1500 ANSI
length increments of 250 mm to 2000 mm  Construction 316 stainless steel Witon elastomer (std.)  Options Silconert treatment (inhibits sulphur and mercury ingression) ICEx Heated version available  Weight (Standard 1" NPT, 500 mm	Connections	connection standard. Flanged connection available up to 1500 ANSI in RF, RTJ, etc. Process connection: 1/4"
& materials  Viton elastomer (std.)  Options  Silconert treatment (inhibits sulphur and mercury ingression)  ICEx Heated version available  Weight  (Standard 1" NPT, 500 mm		increments of 250 mm to
Options Silconert treatment (inhibits sulphur and mercury ingression) ICEx Heated version available Weight (Standard 1" NPT, 500 mm		
,	Options	Silconert treatment (inhibits sulphur and mercury ingression) ICEx Heated version
	Weight	



