

PFP SAMPLE PROBE

Sampler probes are available in a variety of threaded or flanged connection sizes, probe sizes and lengths.

For sampling the end of the tube should be set within the centre 1/3rd of the pipeline.

Tube ends can be straight, 45° or 90°. special purpose ends can be supplied as well.

If the end of the tube has a chamfer or 90° end, the upstream direction of the tube is indicated with an arrow engraved on the upstream side, at the end of the boss.

Specific insertion lengths can be supplied or users can cut the tube to suit the installation. The insertion length can be tagged or engraved on the unit as an option.



Model PFP-3-F



Model PFP1A

Model PFP

Single Probe. 3/8" tube size.

1/4" FNPT process connection.

PFP-1 Line connection 1/2"

PFP-1A Line connection 3/4"

PFP-1B Line connection 1"

PFP-2 as PFP-1/2/3 with large ported needle valve

PFP-3 as PFP-1/2/3 with ball valve

-F as PFP-1/2/3 with flanged connection 150 – 1500 ANSI.



Model PFPF

Pilot Probe. 1/4" FNPT process connections 1/4" tube size. Features 'hot loop' return port. Also available in adjustable model.

Same configuration as PFP models.

Tube end options on all models with tube probe Available with straight bevel or 90° bends.

Tube length should be specified when ordering

Options:

Special coatings

Extension bonnets for severe temperatures

DBB valves.

Heavy wall probe tube



Haldatec

Phone: +61-3-9872-5822 Fax: +61-3-9872-5129
E-mail: sales@haldatec.com.au Web Site: www.haldatec.com.au

